



OPERATION CONTROL
Electronic brightness control & Foot switch control



LED
High power SMD LED's



SAFER
Corrosion resistant AL Body



COOLING SYSTEM
High Capacity fans with AL heat sink

Apollo series LED Film viewers

Salient Features:

- High Power SMD LED's
- Built-in Writing Lamp(Apollo 412 & Apollo 4517)
- Viewing Screen Adjustable Shutters
- Electronic Brightness Control & Foot Switch Control
- Corrosion Resistant AL Body
- As per ASTM E1390

Technical Specifications:

Description	Apollo 258	Apollo 412	Apollo 4517
Viewing Area (LXW)	2.5" X 8" 60mm X 200mm	4" X 12" 100mm X 300mm	4.5" X 17" 110mm X 425mm
Film Density	Up to 4.5 D	Up to 4.5 D	Up to 4.5 D
Uniformity Factor(g)	≥ 0.85	≥ 0.85	≥ 0.85
Input Voltage	110-260 VAC, 50 - 60Hz	110-260 VAC, 50 - 60Hz	110-260 VAC, 50 - 60Hz
Rated Output	90W	150W	240W
Surface Temp.	< 46° C	< 48° C	< 46° C
Dimension (LXWXH)	14.1" X 5.9" X 6.5" 360mm X 150mm X 165mm	18.5" X 6.9" X 7.6" 470mm X 175mm X 195mm	23.6" X 6.9" X 7.6" 600mm X 175mm X 195mm
Housing	Powder Coated Aluminum	Powder Coated Aluminum	Powder Coated Aluminum
Max Brightness	≥ 515,000 Lux/ ≥185,000 cd/m ²	≥ 410,000 Lux/ ≥100,000 cd/m ²	≥ 410,000 Lux/ ≥100,000 cd/m ²
Intensity Control	From 10% - 100%	From 10% - 100%	From 10% - 100%
Cooling	High capacity fans with aluminium heat sink	High capacity fans with aluminium heat sink	High capacity fans with aluminium heat sink
Weight	8.3 lbs(3.8 kg)	8.8 lbs(4 Kg)/12.8 lbs(5.8 Kg) with SMPS	11.6 lbs(5.3 Kg)/17.4 lbs(7.9 Kg) with SMPS

JMD NDT Inc.

450 Century Parkway, Suite# 250 Allen, Texas 75013, USA
T: (908) 224 2858 | E: info@jmdndt.com | W:www.jmdndt.com