



INSTANT ON/OFF OPERATION
No warm-up time for fully intensity



LED
LED's Life Upto (40,000 Hrs)



SAFER
Replaces conventional mercury vapour bulb



COOLING SYSTEM
Cooler than mercury vapour HID bulb with active cooling

LED UV Bulb

Salient Features :


- Replaces conventional mercury vapour bulb
- Long lasting LED's life (40,000 hrs)
- Instant on/off, no warm-up time for full intensity
- Less fragile than conventional mercury vapour HID bulb
- Cooler than mercury vapour HID bulb with active cooling
- UVA pass filter

Technical Specifications:

Light Source	: 3 UVA LED
Wavelength (Peak)	: 365 nm ±5 nm
Constant Intensity at a distance of 15" (38cm)	: ≤ 6,000 μW/cm ²
White Light Emission	: < 10 Lux (0.92 fc)
Beam coverage area	: ≥ Ø200 mm
Power Requirement	: 100V - 264V, 50-60Hz
AC Mains	
Housing	: ABS Plastic
Dimensions	: 6"(15cm) x Ø4.8"(12cm)
Weight	: 0.88lbs (0.4Kg)


Beam Irradiance Pattern & Profile

UVA 150B



Scale 0.5" x 0.5"

3 - LED Array at 15"



- Blue <200 μW/cm²
- Green 200 - 1000 μW/cm²
- Yellow >1000 - 5000 μW/cm²

- Red >5000 - 10000 μW/cm²
- White > 10000 μW/cm²

Kit Contains :

- LED UV Bulb
- Operation Manual & Certificate of Conformity

Order Part No.

- UVA 150B
- Standard Warranty: 6 months



* Subject to terms & conditions Apply

JMD NDT Inc.

450 Century Parkway, Suite# 250 Allen, Texas 75013, USA
T: (908) 224 2858 | E: info@jmdndt.com | W:www.jmdndt.com